

KA28, Cu Set Screw Terminal, #1-4/0 AWG, 1-Hole, 3/8" Stud, 1 Screw

By Burndy Catalog # KA28

Copper Terminal, 1 Hole, 1-4/0 AWG (Str), 3/8" Stud, 1 Screw.

Features

 Compact, high copper alloy terminal for joining cable to equipment pads or terminal blocks

Application

For Joining A Wide Range Of Copper Cable To Equipment Pads Or Terminal Blocks

General

Catalog Number KA28
EU RoHS Indicator Yes
Hardware Type 5 / 8 "
Installation Torque 275 LBS/in

Recommended in-lb

Material Copper

Physical Attribute - Number of 1

Holes

Physical Attribute - Number of 1

Screws

Physical Attribute - Screw Type Allen
Sub Brand KA-LUG
Temperature Rating 194

Type Bolted Lugs & Terminals

UPC 781810364857 UPC 14 Digit GTIN 00781810364857

Dimensions

Dimension - B Length fraction 64/79 in Dimension - Bolt Size fraction 3/8 Dimension - Height fraction 1-1/4 in Dimension - Height inch 1.25 in Dimension - Height mm 31.8 mm Dimension - Hole Size fraction 27/64 Dimension - Hole Size inch 0.42 in Dimension - Hole Size mm 11 mm Dimension - N inch 0.44 in



Dimension - Pad Width inch 0.94 in Dimension - Stud Size inch 3/8

Electrical Ratings

Rating - Minimum Voltage 600

Conductor Related

Conductor - Copper Str Size 1 AWG-4/0 AWG

Range

Conductor Type CU C Str-Size

Certifications And Compliance

Buy America(n) Qualified TAA Compliant (All status valid

till December 2024)

Industry Standard(s) UL 486A-486B Standards - Industry Standards UL 486A-486B

Met

Standards - RoHS Compliance E

Status

UL Listed Yes

Logistics

Carton Quantity 25 Minimum Pack Quantity 1

Product Assets

3D Models - KA28_MODEL-IGES

3D Models - KA28_MODEL-STEP

3D Models - KA28_MODEL-PDF

Catalogs - BURNDY Master Catalog - Section A - Mechanical

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog

Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR KA Lineart

Sales Drawings - SC..074265-01

Specifications - KA28

