

By Burndy  
Catalog # [KA34](#)

Copper Terminal, 1 Hole, 4/0 AWG (Str)-500 kcmil, 1/2" Stud, 1 Screw



**Features**

- Compact, high copper alloy terminal for joining cable to equipment pads or terminal blocks

**Application**

For Joining A Wide Range Of Copper Cable To Equipment Pads Or Terminal Blocks

**Specifications**

EU RoHS Indicator	Yes
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
Industry Standard(s)	UL 486A-486B
UL Listed	Yes
Buy American Compliant	No
Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)

**Conductor**

Conductor - Copper Str Size Range	4/0 Str. - 500 Kcmil
Conductor Type	CU C Str-Size

**Configuration**

Physical Attribute - Number of Holes	1
Physical Attribute - Number of Screws	1

**Dimensions**

Dimension - B Length fraction	1-3/25 in
Dimension - Pad Width inch	1.38 in

Dimension - Height fraction	2-3/32
Dimension - Height inch	2.09 in
Dimension - Height mm	53.1 mm
Dimension - Bolt Size fraction	1/2
Dimension - Hole Size fraction	9/16
Dimension - Hole Size inch	0.56 in
Dimension - Hole Size mm	14 mm
Dimension - Stud Size inch	1/2
Dimension - Mounting	13/16 in
Hardware Bolt Size inch	
Dimension - N inch	0.56 in

**Force Related**

Installation Torque Recommended in-lb	375 LBS/in
---------------------------------------	------------

**General**

Sub Brand	KA-LUG
Physical Attribute - Screw Type	Allen Bolted Lugs & Terminals
UPC 14 Digit GTIN	00781810365854
Hardware Type	13 /16 "
Material	Copper
UPC	781810365854

**Logistics**

Carton Quantity	18
Minimum Pack Quantity	1

**Operational**

Temperature Rating	194
--------------------	-----

**Product Assets**

[Catalog \[English\]](#)