



By Burndy  
Catalog # [KA4C](#)

Copper Terminal, 1 Hole, 14 AWG (Sol)-4 AWG (Str), 1/4" Stud, 1 Screw



Features

- Compact, high copper alloy terminal for joining cable to equipment pads or terminal blocks

Application

For Joining A Wide Range Of Copper Cable To Equipment Pads Or Terminal Blocks

Specifications

|                                    |              |
|------------------------------------|--------------|
| EU RoHS Indicator                  | Yes          |
| Standards - Industry Standards Met | UL 486A-486B |
| Standards - RoHS Compliance Status | EX           |
| Industry Standard(s)               | UL 486A-486B |
| UL Listed                          | Yes          |
| Buy American Compliant             | No           |

Conductor

|                                     |                                                                        |
|-------------------------------------|------------------------------------------------------------------------|
| Conductor - Copper Solid Size       | 14 AWG;13 AWG;12 AWG;11 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG |
| Conductor - Copper Solid Size Range | 14 AWG-4 AWG                                                           |
| Conductor - Copper Str Size         | 14 AWG-4 AWG                                                           |
| Conductor - Copper Str Size Range   |                                                                        |
| Conductor Type                      | CU C Str-Size;AL C Str-Size                                            |

Configuration

|                                       |   |
|---------------------------------------|---|
| Physical Attribute - Number of Holes  | 1 |
| Physical Attribute - Number of Screws | 1 |

Dimensions

|                                |         |
|--------------------------------|---------|
| Dimension - B Length fraction  | 8/17 in |
| Dimension - Pad Width inch     | 0.54 in |
| Dimension - Height fraction    | 3/4     |
| Dimension - Height inch        | 0.77 in |
| Dimension - Height mm          | 19.6 mm |
| Dimension - Bolt Size fraction | 1/4     |
| Dimension - Hole Size fraction | 9/32    |
| Dimension - Hole Size inch     | 0.28 in |
| Dimension - Hole Size mm       | 7 mm    |
| Dimension - Stud Size inch     | 1/4     |
| Dimension - N inch             | 0.25 in |

Force Related

|                     |           |
|---------------------|-----------|
| Installation Torque | 45 LBS/in |
| Recommended in-lb   |           |

General

|                                 |                         |
|---------------------------------|-------------------------|
| Sub Brand                       | KA-LUG                  |
| Material - Hardware             | Steel                   |
| Physical Attribute - Screw Type | Slot                    |
| Type                            | Bolted Lugs & Terminals |
| UPC 14 Digit GTIN               | 00781810361405          |
| Hardware Type                   | 5 / 16 "                |
| Material                        | Copper                  |
| UPC                             | 781810361405            |

Logistics

|                       |      |
|-----------------------|------|
| Carton Quantity       | 1000 |
| Minimum Pack Quantity | 1    |

Product Assets

[Catalog \[English\]](#)