

By Burndy Catalog # KA8C

Copper Terminal, 1 Hole, 14 AWG (Sol)-8 AWG (Str), #10 Stud, 1 Screw



Features

• Compact, high copper alloy terminal for joining cable to equipment pads or terminal blocks

Application

For Joining A Wide Range Of Copper Cable To Equipment Pads Or Terminal Blocks

Specifications

EU RoHS Indicator

Standards - Industry Standards UL 486A-486B

Met

Standards - RoHS Compliance ΕX

Status

Industry Standard(s) UL 486A-486B

UL Listed Yes Buy American Compliant No

Conductor

Conductor - Copper Solid Size 14 AWG:13 AWG:12 AWG:11

AWG;10 AWG;9 AWG;8 AWG

14 Sol. - # 8 Str.

Conductor - Copper Str Size

Range

CU C Str-Size Conductor Type

Dimensions

Dimension - Width inch 0.38 in Dimension - Width mm 9.70 mm Dimension - Pad Width inch 0.38 in 15.42 in Dimension - Height inch Dimension - Height mm 15.5 mm Dimension - Bolt Size fraction #10 Dimension - Hole Size fraction 7/32 Dimension - Hole Size inch 0.21 in Dimension - Hole Size mm 5.3 mm Dimension - Mounting 12.24 UNC Hardware Bolt Size inch

Dimension - N inch 0.19 in

General

Sub Brand KA-LUG Material - Hardware Steel

Physical Attribute - Screw Type Flat head round tip **Bolted Lugs & Terminals**

UPC 14 Digit GTIN 00781810362051

Hardware Type #12 Material Copper UPC 781810362051

Logistics

Carton Quantity 100 Minimum Pack Quantity 1

Product Assets

Catalog [English]

