



Manual starter, integral horsepower, NEMA M0, 600VAC, 3 pole, 5HP at 380/575VAC, 3 phase, no indicator, NEMA 1

2510MBG2

Product availability: Stock - Normally stocked in distribution facility

Main

Product	Manual Starter
Туре	М
NEMA Size	M-0

Complementary

Control Unit	Push-button	
Pilot Light	No indicator	
Horsepower Rating	3 hp 200230 V AC, 3 phase 5 hp 380575 V AC, 3 phase	
Voltage Rating	600 V AC	
Number of Poles	3P	
Starter Type	Non reversing	
Electrical Connection	Pressure wire clamp	
Overload Relay Type	Melting alloy	
Number of Thermal Units Required	3	
Wire Gauge	AWG 14AWG 8 copper	
Auxiliary Contacts	Uden	
Height	8.63 in (219.20 mm)	
Width	5 in (127 mm)	
Depth	4.13 in (104.90 mm)	
Net Weight	4.14 lb(US) (1.88 kg)	

Environment

Certifications	CSA LR60905 class 3211 05 UL listed file E42243 CCN NLRV
NEMA Enclosure Rating	NEMA 1 painted sheet steel

Ordering and shipping details

Category	US10CP121103
Discount Schedule	0CP1
GTIN	785901792536
Returnability	Yes

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Country of origin MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.70 in (11.938 cm)
Package 1 Width	5.60 in (14.224 cm)
Package 1 Length	9.20 in (23.368 cm)
Package weight(Lbs)	4.101 lb(US) (1.860 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	126
Package 2 Height	40.00 in (101.600 cm)
Package 2 Width	40.00 in (101.600 cm)
Package 2 Length	48.00 in (121.920 cm)
Package 2 Weight	535.0006 lb(US) (242.672 kg)

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better


Materials and Substances		
Packaging made with recycled cardboard	No	
Packaging without single use plastic	No	
EU RoHS Directive	Compliant with Exemptions	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
PVC free	Yes	

Use Again

○ Repack and remanufacture	
Take-back	No


Dimensions Drawings

Approximate Dimensions



Technical Illustration

Wiring diagram



3-Pole, 3-Phase

Jul 22, 2025