



Contactor, Type S, multipole lighting, electrically held, 30A, 3 pole, 220/240VAC 50/60Hz coil, NEMA 1 [TAA]

8903SMG2V03

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product	Electrically Held Lighting Contactor	
Туре	S	

Complementary

•	
Control Circuit Voltage	240 V AC 60 Hz 220 V AC 50 Hz
Current Rating	30 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Uden
Other Options	None
Electrical Connection	Lugs
Height	10 in (254 mm)
Depth	5.3 in (134 mm)
Width	6.0 in (152 mm)

Environment

Enclosure Type	NEMA 1 painted sheet steel surface none	
Product Certifications	UL Listed CSA	

Ordering and shipping details

Category	US10CP121325	
Discount Schedule	0CP1	
GTIN	785901619550	
Returnability	No	
Country of origin	MX	

Packing Units

Unit Type of Package 1	PCE	
Nhr of units in nka	1	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Height	6.30 in (16.002 cm)	
Package 1 Width	6.50 in (16.51 cm)	
Package 1 Length	10.60 in (26.924 cm)	
Package weight(Lbs)	6.321 lb(US) (2.867 kg)	

Compliance

Compliance TAA

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Not compliant

Use Again

○ Repack and remanufacture	
Take-back	No