



Contactor, Definite Purpose, 30A, 3 pole, 20HP at 575VAC, 3 phase, 208/240VAC 60Hz 220VAC 50Hz coil, open

8910DPA33V09

Product availability: Stock - Normally stocked in distribution facility

Main

Product or Component Type	Definite Purpose Contactor	
Line Rated Current	30 A	
Number of Poles	3P	
Pole contact composition	3 NO	
Range of Product	DPA	

Complementary

· · · · · · · · · · · · · · · · · ·		
Maximum Horse Power Rating	2 hp 115 V AC, 1 phase	
	5 hp 230 V AC, 1 phase	
	10 hp 230 V AC, 3 phase	
	15 hp 460 V AC, 3 phase	
	20 hp 575 V AC, 3 phase	
Locked rotor rated current	150 A 460 V AC	
	120 A 575 V AC	
	180 A 277 V AC	
[Ue] rated operational voltage	600 V AC	
[Uc] control circuit voltage	208240 V AC 60 Hz	
	220 V AC 50 Hz	
Phase	3 phase	
Electrical Connection	Quick connect terminals Binder head	

Environment

Product Certifications	UL Recognized	
	CSA	

Ordering and shipping details

Category	US1CP1B21343
Discount Schedule	CP1B
GTIN	785901073529
Returnability	Yes

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.20 in (13.208 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Width	6.70 in (17.018 cm)
Package 1 Length	8.00 in (20.320 cm)
Package weight(Lbs)	8.479 lb(US) (3.846 kg)
Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Height	5.50 in (13.970 cm)
Package 2 Width	6.90 in (17.526 cm)
Package 2 Length	8.50 in (21.590 cm)
Package 2 Weight	8.430 lb(US) (3.824 kg)

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	9635bca0-88f5-4211-aaa3-d012e1850a41

Use Again


○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No

Product data sheet

8910DPA33V09

Technical Illustration

Dimensions



ALL DIMENSIONS ARE APPROXIMATE. REFER TO TECHNICAL DRAWINGS AND DOCUMENTATION FOR COMPLETE INFORMATION.

Technical Illustration

Wiring diagram

